

HU ES 10 B Scissor pallet truck with electric-hydraulic lift

Capacity 1000 kg,

fork height max. 800 mm

The HU ES 10 B increases the usefulness of the HU HS 10 B by saving operating time for demanding applications with frequent lifting and lowering operations.


Features


- Ergonomic control button for the hydraulic unit fitted in the handle.
- In case of a battery failure the manual use of lifting and lowering is still guaranteed.
- Quick electric-hydraulic lifting of the load, pressure relief valve protects against overloading.
- Low noise and smooth running due to polyurethane steering and load rollers as standard.
- Additional tilting protection for the load rollers.

Scope of delivery

• Battery and integrated battery charger







Technical data HU ES 10 B

| Model | HU ES 10 B |
|---|------------|
| ArtNo. | N26900020 |
| Capacity Q, kg | 1000 |
| Load center c, mm | 600 |
| Weight, kg | 152 |
| Tyre type ¹ | PUR/PUR |
| Steering rollers, mm | 180 x 50 |
| Load rollers, mm | 75 x 50 |
| Number of wheels/load rollers | 2/2 |
| Stroke h3, mm | 715 |
| Height of control handle max. h14, mm | 1254 |
| Fork height lowered h13, mm | 85 |
| Overall length I1, mm | 1715 |
| Overall width b1/b2, mm | 575 |
| Fork height s, mm | 45 |
| Fork width e, mm | 160 |
| Fork length I, mm | 1170 |
| Outside dimension of forks b5, mm | 540 |
| Ground clearance, wheelbase centre m2, mm | 18 |
| Aisle width pallet Ast, mm | 1986 |
| Turning circle radius Wa, mm | 1564 |
| Battery charger, V/A | 220/6 |
| Battery voltage, capacity K5, V/Ah | 12/52 |

¹PUR...Polyurethane