



HX 150

HX Scissor elevating platform, mobile with single scissor

Capacity 150 - 750 kg,
platform height max. 1000 mm

For the independant lifting and supplying of loads within a warehouse environment.

Features

- Hydraulic lifting of the load with foot pedal.
- Lowering speed can be finely metered for sensitive lowering of the load.
- Ergonomic handlebar for easy operation, tiltable for model HX 150.
- Steering roller with brake for safe parking of the hand stacker.
- Robust construction with hard chromium plated piston and pressure relief valve.

Technical data HX

| Model | HX 150 | HX 300 | HX 500 | HX 750 |
|--|----------|----------|----------|----------|
| Art.-No. | 34600020 | 40057357 | 40057358 | 40057360 |
| Capacity, kg | 150 | 300 | 500 | 750 |
| Platform height max. $h_3 + h_{13}$, mm | 720 | 880 | 880 | 1000 |
| Platform height min. h_{13} , mm | 220 | 285 | 285 | 420 |
| Stroke h_3 , mm | 500 | 595 | 595 | 580 |
| Lifting height per pump stroke, mm | 27 | 31 | 31 | 15 |
| Overall height h_1 , mm | 960 | 984 | 984 | 990 |
| Overall length L_1 , mm | 908 | 1093 | 1093 | 1330 |
| Overall width b_1 , mm | 450 | 500 | 500 | 600 |
| Platform length P_1 , mm | 700 | 850 | 850 | 1000 |
| Platform width P_2 , mm | 450 | 500 | 500 | 510 |
| Tyre type ¹ | PUR/PUR | PUR/PUR | PUR/PUR | PUR/PUR |
| Rollers, mm | 100 x 36 | 128 x 40 | 128 x 40 | 147 x 50 |
| Number of wheels/load rollers | 2/2 | 2/2 | 2/2 | 2/2 |
| Weight, kg | 49 | 78 | 82 | 120 |

¹PUR... Polyurethane

