

PRAKTIKUS HP Platformlift, mobile

Capacity 400 kg,
platform height max. 1200 mm

For the occasional, internal application of lifting and transporting of goods.

Features

- Easy lifting by tiltable foot pedal.
- Lowering speed can be finely metered for sensitive lowering of the load.
- Ergonomic handlebar for easy operation.
- Steering roller with brake for safe parking of the hand stacker.
- Robust construction with chrome plated chassis, hard chromium plated piston and pressure relief valve.
- Covered chain deflection for increased safety.



Technical data PRAKTIKUS HP

Model	HP 0412
Art.-No.	40008779
Capacity, kg	400
Platform height max. $h_3 + h_{13}$, mm	1200
Platform height min. h_{13} , mm	200
Freelift h_2 , mm	1000
Stroke h_3 , mm	1000
Lifting height per pump stroke, mm	23
Overall height h_1 , mm	1310
Overall length L_1 , mm	1037
Overall width b_1 , mm	590
Platform length P_1 , mm	650
Platform width P_2 , mm	550
Tyre type ¹	VG/VG
Steering rollers, mm	150 x 45
Load rollers, mm	150 x 45
Number of wheels/load rollers	2/2
Ground clearance m_1 , mm	50
Wheelbase y , mm	785
Weight, kg	71

¹ VG... Solid rubber

