

General Purpose Cylinders (Single Acting)

Capacity: 5 – 95 Ton
Stroke: 16 – 362 mm



Enerpac RC Series



Model Number	Capacity Class (Ton)	Closed Height (mm)	Stroke (mm)	Outside Dia. (mm)	Oil Req. (cm ³)	Weight (kg)
RC-50	5	41	16	58	10	1.0
RC-51	5	110	25	38	16	1.0
RC-53	5	165	79	38	50	1.5
RC-55	5	216	127	38	83	1.9
RC-57	5	273	177	38	115	2.4
RC-59	5	324	232	38	151	2.8
RC-101	10	90	26	57	38	1.8
RC-102	10	121	54	57	78	2.3
RC-104	10	171	105	57	152	3.3
RC-106	10	248	156	57	226	4.4
RC-108	10	298	203	57	294	5.4
RC-1010	10	349	257	57	373	6.4
RC-1012	10	400	304	57	441	6.8
RC-1014	10	451	356	57	516	8.2
RC-151	15	124	25	70	51	3.3
RC-152	15	149	51	70	104	4.1
RC-154	15	200	101	70	205	5.0
RC-156	15	271	152	70	308	6.8
RC-158	15	322	203	70	411	8.2
RC-1510	15	373	254	70	516	9.5
RC-251	25	140	26	86	86	5.9
RC-252	25	165	50	86	166	6.4
RC-254	25	216	102	86	339	8.2
RC-256	25	273	158	86	525	10.0
RC-258	25	324	210	86	697	12.2
RC-2510	25	375	261	86	867	14.1
RC-2512	25	425	311	86	1033	16.3
RC-2514	25	476	362	86	1202	17.7
RC-308	30	387	209	102	880	18.1
RC-502	50	176	51	127	362	15.0
RC-504	50	227	101	127	719	19.1
RC-506	50	283	159	127	1131	23.1
RC-5010	50	384	260	127	1855	31.8
RC-5013	50	460	337	127	2399	37.6
RC-756	75	286	156	146	1601	29.5
RC-7513	75	492	333	146	3417	59.0
RC-1002	95	219	51	178	676	36.7
RC-1006	95	357	168	178	2239	5.9