

High Tonnage Cylinders (Single Acting)



Model Number	Capacity Class (Ton)	Closed Height (mm)	Stroke (mm)	Outside Dia. (mm)	Oil Req. (cm3)	Weight (kg)
HCG-506	50	283	150	130	1,178	24
HCG-1004	100	252	100	175	1,431	40
HCG-1006	100	302	150	175	2,147	46

HCG Series

High Tonnage Lock Nut Cylinders (Single Acting)



Model Number	Capacity Class (Ton)	Closed Height (mm)	Stroke (mm)	Outside Dia. (mm)	Oil Req. (cm3)	Weight (kg)
HCL-504	50	214	100	130	785	22
HCL-506	50	264	150	130	1,178	27
HCL-5010	50	364	250	130	1,963	38
HCL-1006	100	287	150	175	2,147	54
HCL-2006	200	338	150	250	4259	124
HCL-2506	250	349	150	280	5,446	167

When using a High Tonnage Lock Nut Cylinder, add a V-66 manual check valve for additional safety

HCL Series

Additional sizes are available on request

Low Height Lock Nut Cylinders with Tilt Saddles (Single Acting)



Model Number	Capacity Class (Ton)	Closed Height (mm)	Stroke (mm)	Outside Dia. (mm)	Oil Req. (cm3)	Weight (kg)
LPL-602	60	126	50	140	433.0	15
LPL-1002	100	137	50	173	715.7	25
LPL-1602	150	148	45	220	1021.4	43
LPL-2002	200	155	45	245	1275.9	55

When using a Lock Nut Cylinder, add a V-66 manual check valve for additional safety

LPL Series

Additional sizes are available on request